

1-inch exit ferrite magnet compression driver

- 2,200Hz recommended min. crossover freq (12dB/oct)
- Single piece PETP diaphragm and surround

30W

Continuous
power rating

107dB

sensitivity

1-inch

Copper clad
aluminium coil
voice

General Specifications	
Power Rating	15W
Continuous power rating	30W
Rated impedance	8 ohm
Sensitivity	107dB
Frequency range	1500-20,000Hz
Recommended min. crossover (12 dB/oct)	2200Hz
Magnet type	Ferrite
Voice coil diameter	25mm / 1in
Voice coil material	Copper clad aluminium
Diaphragm material	PETP film
Surround material	PETP film

Mounting Information	
Width	90mm / 3.5in
Depth	52.8mm / 2.1in
Fitting	Screw (35mm/1.38in diameter)
Throat exit	25mm / 1in
Unit weight	0.8kg / 1.8lb

Packed Dimensions & Weight	
Single pack size W x D x H	113mm x 103mm x 72mm / x 4.4in 4.0in x 2.8in
Single pack weight	1.1kg / 2.4lb
Multi pack qty	16
Multi pack size W x D x H	480mm x 480mm x 75mm / x 18.9in 18.9in x 2.95in
Multi pack weight	15kg / 33lb

Horns	
T5951	H1SC9050 Horn
T5952	H1SC7050 Horn

Frequency Response and Impedance Curves

